

Product name	Vinyl acetate		EU/EN
MSDS number	80094	Revision Date	Jul.02.2009***
Revision Number	4***.01***	Issuing date	Jul.02.2009***

1. Identification of the substance/preparation and the company/undertaking

Product name
Vinyl acetate***

Manufacturer, importer, supplier
Celanese Chemicals Europe GmbH
Frankfurter Straße 111
D-61476 Kronberg/Ts.***

Product Information
PS.Chemicals.EU@celanese.com***

Emergency telephone number
+49 (0)69-305 6418***

End use:
Chemical intermediate (including monomers)***

2. Hazards identification

Indication of danger Highly flammable

R-phrases(s) ***
R11 - Highly flammable. ***

3. Composition/information on ingredients

Components	CAS-No	EC-No.	Classification	Percent %
Vinyl acetate	108-05-4	203-545-4	F;R11	99.9 min.

Remarks Hydroquinone is present at 3 - 30 ppm as a polymerization inhibitor. Monomethyl ether of hydroquinone may be present upon request.***

4. First aid measures

General Information Remove contaminated, soaked clothing immediately and dispose of safely. Pay attention to own protection. In any case show the physician the Safety Data Sheet***

Inhalation Keep at rest. Move to fresh air. Call a physician immediately***

Skin Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. If symptoms persist, call a physician***

Product name	Vinyl acetate		EU/EN
MSDS number	80094	Revision Date	Jul.02.2009***
Revision Number	4***.01***	Issuing date	Jul.02.2009***

Eyes Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Call a physician immediately***

Ingestion Rinse with plenty of water. If conscious, drink plenty of water. If swallowed, do not induce vomiting - seek medical advice***

Notes to physician***

Main symptoms Vapours may cause irritation to the eyes, respiratory system and the skin, Gastrointestinal discomfort***.

Special hazard respiratory disorder***.

Treatment Treat symptomatically. In case of lung irritation first treatment with dexametason aerosol (spray). In case of choking: administration of activated charcoal and a saline laxative agent.. In the case of absorption of large volumes, use gastroscopy with suction cleaning***

5. Fire-fighting measures

Suitable extinguishing media

foam. Dry chemical. carbon dioxide (CO2)***

Extinguishing media which must not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire***

Special exposure hazards arising from the substance or preparation itself, its combustion products, or released gases

Under conditions giving incomplete combustion, hazardous gases produced may consist of carbon monoxide
carbon dioxide (CO2)
Combustion gases of organic materials must in principle be graded as inhalation poisons
Vapors are heavier than air and may spread along floors***

Special protective equipment for fire-fighters

self-contained breathing apparatus (EN 133)***

Environmental precautions

Water runoff can cause environmental damage. Dike and collect water used to fight fire***

Other Information

Cool containers / tanks with water spray***

6. Accidental release measures

Personal precautions

Avoid contact with the skin and the eyes. Keep away from heat and sources of ignition. Provide adequate ventilation***

Environmental precautions

Prevent further leakage or spillage. Do not discharge into the drains/surface waters/groundwater. Material creates a special hazard because it floats on water.. Caution: Spontaneous polymerization can occur if material is released or mixed with incompatibles.***

Safety data sheet according to regulation (EG) Nr. 1907/2006



Product name	Vinyl acetate		EU/EN
MSDS number	80094	Revision Date	Jul.02.2009***
Revision Number	4***.01***	Issuing date	Jul.02.2009***

Methods for cleaning Up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal. Dispose of in accordance with local regulations***

7. Handling and storage

Handling

Advice on safe handling

Provide sufficient air exchange and/or exhaust in work rooms***

Protection - fire and explosion:

Keep away from sources of ignition - No smoking. Take necessary action to avoid static electricity discharge. Ground and bond containers when transferring material. In case of fire, emergency cooling with water spray should be available.

Blanketing vinyl acetate under an inert atmosphere eliminates flammable vapor in the head space and contamination with atmospheric moisture.. Bulk storage of vinyl acetate at ambient temperatures is an acceptable practice when there is a routine turnover of the tank contents every 60 days or less. Inhibitor levels should be monitored if a stability problem is suspected.***

Temperature class

T2***

Storage

Technical measures/Storage conditions

Keep tightly closed in a dry, cool and well-ventilated place. Handle and open container with care. Store at temperatures not exceeding 30 °C/ 86*** °F***

Incompatible products

oxidizing agents, radical initiators, strong acids, amines***

German storage class

3A: Flammable liquids***

8. Exposure controls / personal protection

National occupational exposure limits (Germany)

Components	TRGS 900 (AGW)		STEL Factor
Vinyl acetate	18 mg/m ³ ***	5 PPM***	2***

TRGS 905 / 907***

Components	Carcinogenic	Mutagenic	Embryonic Toxin	Toxic to reproduction
Vinyl acetate	3 ***	-	-	-

ACGIH Exposure Limits

Components	TWA
Vinyl acetate	10 PPM***

Safety data sheet
according to regulation (EG) Nr. 1907/2006



Product name	Vinyl acetate		EU/EN
MSDS number	80094	Revision Date	Jul.02.2009***
Revision Number	4***.01***	Issuing date	Jul.02.2009***

Components	STEL
Vinyl acetate	15 PPM***

Engineering measures General or dilution ventilation is frequently insufficient as the sole means of controlling employee exposure. Local ventilation is usually preferred. Explosion-proof equipment (for example fans, switches, and grounded ducts) should be used in mechanical ventilation systems***

Personal protective equipment

General advice Avoid contact with skin and eyes. Do not breathe vapors or spray mist. Use only in an area equipped with a safety shower. Hold eye wash fountain available***

Hygiene measures When using, do not eat, drink or smoke. Take off all contaminated clothing immediately. Wash hands before breaks and immediately after handling the product***

Respiratory protection respirator with A/PA*** filter***

Eye protection Tightly fitting safety goggles. In addition to goggles, wear a face shield if there is a reasonable chance for splash to the face. Equipment should conform to EN 166***

skin protection impervious clothing***

Hand protection Chemicals resistant gloves***
Type Butoject*** (Company KCL) or comparable article;
 or refer to glove manufacturer's recommendation***
Evaluation according to EN 374: level 4*****
Material thickness approx 0.3*** mm***
Break through time approx 120*** min***
Suitable material butyl-rubber ***

9. Physical and chemical properties

Appearance
Form liquid***
Colour colourless***
Odor sweet***

Flash point -8***°C***
Method closed cup***
Ignition temperature 385°C
Method DIN 51794***

Lower explosion limit 2.6 Vol. %
Upper explosion limit 13.4 Vol. %

Product name	Vinyl acetate	Revision Date	EU/EN
MSDS number	80094	Issuing date	Jul.02.2009***
Revision Number	4***.01***		Jul.02.2009***

Melting point/range	-93.2***°C***
Boiling point/range	72°C @ 1013 hPa
Density	0.93 g/ml @ 20°C***
pH	Neutral
Viscosity	0.43*** mPa*s @ 20°C***
vapor pressure	120 hPa @ 20°C*** 445*** hPa @ 50°C***
vapor density	3.0*** (Air=1)***
Water solubility	20*** g/l @ 20°C
Partition coefficient (n-octanol/water)	0.73 (measured) Hansch/Leo

10. Stability and reactivity

Stability	Stable under normal conditions of handling, use and transportation.***
Conditions to avoid	Avoid any source of ignition.. Avoid contact with heat, sparks, open flame, and static discharge.. Avoid temperatures above 30 °C / 86*** °F***
Materials to avoid	Keep away from:., oxidizing agents, radical initiators , strong acids, amines***
Thermal decomposition	No decomposition if used as directed. If heated to thermal decomposition the following decomposition products may occur depending on the conditions. carbon oxides.
Hazardous reactions	Polymerization can occur. May polymerize violently or explosively if contaminated or overheated. . Uncontrolled polymerization can cause rapid evolution of heat and increased pressure which can result in violent rupture of storage vessels or containers.***

11. Toxicological information

Vinyl acetate

Oral		LD50: 2920 mg/kg, rat***
Dermal		LD50: 2335 mg/kg, rabbit***
Inhalation		LC50: 4000 ppm, rat, 4h***
Skin irritation		Mild skin irritation***
	Species	rabbit
	Method	OECD 404
Skin Sensitization		nonsensitizer
	Species	mouse
	Method	OECD 429
Eye Irritation		Mild eye irritation
	Species	rabbit eye
	Method	OECD 405

Product name	Vinyl acetate	Revision Date	EU/EN
MSDS number	80094	Issuing date	Jul.02.2009***
Revision Number	4***.01***		Jul.02.2009***

11. Toxicological information

Carcinogenic effects

Has been shown to cause cancer in lifetime rat inhalation and rat and mouse drinking water studies at the site of contact at non-physiologically relevant doses***

Carcinogenic Effects

No evidence of carcinogenicity***
mice***

Species

inhalation lifetime study***

Study

Positive and negative results***

in vitro Mutagenicity

Both positive and negative results***

in vivo Mutagenicity

Not a mutagenic concern in human at physiologically relevant routes of entry***

Reproductive toxicity

No toxicity to reproduction***

Routes of exposure

oral drinking water

Species

rat

Developmental effects

no adverse developmental effects***

Routes of exposure

oral drinking water and Inhalation***

Species

rat

Repeated exposure

28-day and 90-day effect respiratory tract irritation extensive degeneration of upper respiratory tract epithelium Degeneration of the olfactory mucosa was observed***

Routes of exposure

Inhalation***

Species

rats***

12. Ecological information

Vinyl acetate

Toxicity to fish

LC50: 19 mg/l (96h)

Species

Pimephales promelas (Fathead minnow)

LC50: 18 mg/l (96h)

Species

Lepomis macrochirus (Bluegill sunfish)

Toxicity to daphnia

EC50: 12.6 mg/l (48h)

Species

Daphnia magna

Toxicity to algae

EC50: 8.8 mg/l (72h)

Species

Selenastrum capricornutum (green algae)

Toxicity to bacteria

EC50: 6.0 mg/l

Biodegradation

51 - 62 % % (5d)

Bioconcentration factor (BCF)

2

Bioaccumulation

Bioaccumulative potential - low

13. Disposal considerations

Product information

Disposal required in compliance with all waste management related state and local regulations. The choice of the appropriate method of disposal depends on the product composition by the time of disposal as well as the local statutes and possibilities for disposal.***

Product name	Vinyl acetate		EU/EN
MSDS number	80094	Revision Date	Jul.02.2009***
Revision Number	4***.01***	Issuing date	Jul.02.2009***

Uncleaned empty packaging Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.***

14. Transport information

ADR/RID

UN/ID No.	UN 1301
Proper Shipping Name	Vinyl Acetate, stabilized
Hazard Class	3
Packing group	II
Tunnel Restriction Code	(D/E)***
Hazard Number	339

ADNR

ADNR	ADNR: Container and Tanker
UN/ID No.	UN 1301
Proper Shipping Name	Vinyl Acetate, stabilized
Hazard Class	3
Packing group	II

ICAO/IATA

UN-No.	UN 1301*****
Proper Shipping Name	Vinyl Acetate, stabilized ***
Hazard Class	3
Packing group	II

IMDG

UN/ID No.	UN 1301*****
Proper Shipping Name	Vinyl Acetate, stabilized ***
Hazard Class	3
Packing group	II
EmS Code	F-E, S-D

15. Regulatory information

Labelling in accordance with EC directives

EC label ***

Symbol(s) F - Highly flammable.

R-phrase(s) ***
R11 - Highly flammable. ***

S-phrase(s) ***
S16 - Keep away from sources of ignition - No smoking.
S23.2 - Do not breathe vapour.
S29 - Do not empty into drains.
S33 - Take precautionary measures against static discharges. ***

Product name	Vinyl acetate		EU/EN
MSDS number	80094	Revision Date	Jul.02.2009***
Revision Number	4***.01***	Issuing date	Jul.02.2009***

Water Hazard Class (WGK):

WGK Class 2***
WGK Reg-Nr. 203
WGK Source Classification according to VwVwS, Annex 1 or 2

16. Other information

R-phrases(s) ***

R11 - Highly flammable. ***

For further information, see:

For more information, other material safety data sheets or technical data sheets please consult the Celanese homepage (www.celanese.com)***

Other Information:

- Observe national and local legal requirements***

Changes against the previous version are marked by *****

Sources of key data used to compile the datasheet

Information contained in this safety data sheet is based on Celanese owned data and public sources deemed valid or acceptable. The absence of data elements required by ANSI or 1907/2006 indicates, that no data meeting these requirements is available***

Further information

This information is based on our present state of knowledge. It shall describe our products regarding safety requirements and shall not be construed as a guarantee or statement of condition and/or quality***