

GRADESHEET

ATEVA® STANDARD GRADES

ETHYLENE VINYL ACETATE COPOLYMERS

Ateva Grades	% VA	Melt Index (g/10 min.)	Adhesives	Automotive	Coating Lamination	Compounds	Flexible Packaging	Foam	Molding	Tubing	Photovoltaic	Wire & Cable
2842AC	28	400	●									
2850A	28	850	●									
2803W	28	3										●
2803ASB	28	3				●						
2803A	28	3				●		●				
3325A	33	43								●		
3325AC	33	43	●									
9030	33	43								●		
3342AC	33	400	●									
3325ACX	33	43										●
4030AC	40	55	●									
4030ACX	40	55										●

LOW DENSITY POLYETHYLENE (LDPE)

Grades	Density	Melt Index (g/10 min.)	Adhesives	Automotive	Coating Lamination	Compounds	Flexible Packaging	Foam	Molding	Tubing	Photovoltaic	Wire & Cable
505	0.924	0.3				●			●			
525	0.922	0.8				●			●			
220	0.921	2							●			
520	0.921	2				●						●
280	0.917	20	●						●			
190	0.914	70	●	●	●							
191A	0.913	160	●	●	●							
192	0.913	220	●	●	●							
193	0.912	400	●	●	●							
472	0.917	7				●						
418	0.916	12.7				●						

CELANESE EVA POLYMERS

222 W. Las Colinas Blvd.
Suite 900N
Irving, TX 75039

ALL REGIONS

CUSTOMER SERVICE

t: 1-800-661-3663
e: orderseva@celanese.com

MANUFACTURING

Edmonton, Alberta Canada

ALL REGIONS

TECHNOLOGY AND PRODUCT STEWARDSHIP

8040 Dixie Highway
Florence, KY 41042
1-859-525-4740
Email: eva.techservice@celanese.com

© 2016 Celanese or its affiliates. All rights reserved.

This publication was printed based on Celanese's present state of knowledge, and Celanese undertakes no obligation to update it. Because conditions of product use are outside Celanese's control, Celanese makes no warranties, express or implied, and assumes no liability in connection with any use of this information. Nothing herein is intended as a license to operate under or a recommendation to infringe any patents.

Celanese®, registered C-ball design and all other trademarks identified herein with ®, TM, SM, unless otherwise noted, are trademarks of Celanese or its affiliates.