

AVICOR® 2550

A VERSATILE 100% ACRYLIC POLYMER EMULSION

THE OPTIMUM CHOICE FOR HIGH PERFORMANCE AND VERSATILITY

Avicor® 2550 is a pure acrylic emulsion designed for high performance and versatility in a wide range of coating formulations, including interior and exterior paints. This resin responds effectively to associative thickeners and helps produce paints with outstanding durability and gloss, offering superior wet and dry adhesion characteristics.

Typical Properties*	
Solid content	50%
Viscosity	50-300 cP
Average particle size	150 nm
Tg	20° C
MFFT	17° C
pH	8.5
APE-free	No
Film on glass	Clear

*These values are typical and do not constitute specifications.

Avicor® 2550 can be used to make durable interior paints across all sheen levels where high scrub resistance is desired. This emulsion also provides good weathering resistance, resistance to cracking and good gloss retention in exterior paints.

Celanese has the experience and expertise to help you choose the right emulsion for your coating formulations, while providing the right balance between performance and cost.

APPLICATIONS

- Interior paints
- Exterior paints

KEY FEATURES

- Excellent thickener response
- Interior and exterior capability
- Superior scrub and stain resistance
- Good wet and dry adhesion
- Very good weatherability

Celanese

222 W. Las Colinas Blvd., Irving, TX 75039
 t: +1-877-832-7782 (Technical Service)
 t: +1-800-845-0940 (Customer Service)
 w: celanese.com/emulsion-polymers

Celanese Emulsions Technical Center

8040 Dixie Highway, Florence, KY 41042
 e: emulsionstechservice@celanese.com

Copyright © 2018 Celanese or its affiliates. All rights reserved. Celanese ®, registered C-ball design and all other trademarks identified herein with the ®, TM, SM, unless otherwise noted, are trademarks of Celanese or its affiliates.

This publication was printed January, 2018 based on Celanese's present state of knowledge, and Celanese undertakes no obligation to update it. Because conditions of product use are outside Celanese's control, Celanese makes no warranties, express or implied, and assumes no liability in connection with any use of this information. Nothing herein is intended as a license to operate under or a recommendation to infringe any patents.
 EMUL-034-Avicor2550-SS-EN-0118

