

**Description:**

brochure.

- This is a vinyl acetate/ethylene copolymer emulsion designed for use as a base resin for general purpose construction adhesives and sealants. This polymer exhibits good pigment binding characteristics and provides excellent adhesion to a variety of porous and non-porous substrates. Films of this emulsion are inherently flexible, yet non-tacky.
- TufCOR®4510 has excellent compatibility with styrene butadiene emulsions so it can be used in the same mixing equipment and transfer lines without compatibility issues.

Typical Properties	
Solids	55%
Viscosity <sup>1</sup>	125 cps
pH	6.5
Tg (°C)	+9
Density	8.9 lbs/gal
Mechanical stability	Excellent
Compatibility with SBR	Excellent

<sup>1</sup> Brookfield RVF, @ 77°F

**Suggested Applications:**

- General purpose construction adhesives
- Adhesives mastics
- Caulks and sealants
- Cove base adhesives

**Storage & Handling:**

- Shelf life is approximately six months at 77° F.
- Consult MSDS for important health, safety and handling information before using this product.
- Consult Celanese's *Storing, Handling and Preserving Emulsion Products*



**Version: April 2014**

8040 Dixie Highway, Florence, KY 41042 • Technical Service 877-832-7782 • Customer Service: 800-845-0940  
emulsionstechservice@celanese.com • www.celanese-emulsions.com

Copyright © 2014. Celanese or its affiliates. All rights reserved.

This publication was printed based on Celanese's present state of knowledge, and Celanese undertakes no obligation to update it. Because conditions of product use are outside Celanese's control, Celanese makes no warranties, express or implied, and assumes no liability in connection with any use of this information. Nothing herein is intended as a license to operate under or a recommendation to infringe any patents.

© 2014 Celanese, [the C-ball design] and [TufCOR] are registered trademarks of Celanese or its affiliates.