

## Sales Specification

# Vinyl Acetate

### Specifications

		<u>Limits</u>
Vinyl Acetate, wt.% <sup>1</sup>	min.	99.9
Water, wt.%	max.	0.04
Color, Pt-Co Units	max.	5
Acidity, as Acetic Acid, wt.%	max.	0.005
Aldehydes, as Acetaldehyde, wt.%	max.	0.010
Distillation Range, °C (including 72.7)	max.	0.5
Hydroquinone, ppm <sup>2</sup>		3-5 or 14-17

### References:

1 By Difference – 100.0% minus (acid plus water plus impurities as determined by Gas Chromatography).

2 Alternate inhibitor packages are available on request.

Test methods used for each specification analysis are available. Contact your Sales Person or Customer Service Representative to request information

#### Product Numbers:

50002030 (HQ 3-5)

50001532 (HQ 14-17)

Reviewed: August 2009

Revised: Aug 2009

Supersedes: April 1998

Celanese Pte Ltd  
60 Anson Road, Maple Tree  
Anson #13-02,  
Singapore 079914  
Tel: (65) 6513-0443  
Fax: (65) 6227-8397

Celanese (Shanghai)  
International Trading Co. Ltd  
Room 411, No. 473 Fu Texi 1st  
Road, Waigaoqiao Free Trade  
Zone, Shanghai, China  
Tel: (86) 21-3861-9288  
Fax: (86) 21-3861-9588

Celanese Chemicals (North  
America)  
1601 West LBJ Freeway  
Dallas, TX 75234  
Tel: 1-972-443-4000

Celanese Chemicals (Europe  
GmbH)  
Frankfurter Straße 111  
61476 Kronberg im Taunus  
Deutschland / Germany Tel:  
Tel: +49 (0) 6107 772 0  
FAX: +49 (0) 6107 772 7204

This information is based on our present state of knowledge and is intended to provide general notes on our products and their uses. It should therefore not be construed as guaranteeing specific properties of the products described or their suitability for a particular application. Any existing industrial property rights must be observed. The quality of our products is guaranteed under our General Conditions of Sale.