

Product name	CoolPoly®		NAGH/EN
MSDS number	87110055	Revision Date	Sep.11.2016***
Revision Number	0***	Issuing date	Oct.30.2017***

1. Product and company identification

Trade Name

CoolPoly®

The following SDS applies to products described by combinations of the following trade name, product grade and color code listed below.

Product Grade(s):

D8102

Manufacturer, importer, supplier

Ticona Polymer, Inc.
 A business of Celanese
 8040 Dixie Hwy.
 Florence, KY 41042
 United States
 www.celanese.com

Transportation emergency phone numbers:

In USA, call 800 424 9300
 Outside USA, call +001 703 527 3887, collect calls accepted.

Product Information

1-800-833-4882
 info-engineeredmaterials-am@celanese.com

Synonyms:

Thermoplastic polyester elastomer / TPE-E

Identified uses

Plastic processing industry.

2. Hazard Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200:

This material is not hazardous under the criteria of the Federal OSHA Hazard Communication Standard (29CFR 1910.1200)

3. Composition/information on ingredients

Chemical characterization Thermoplastic polyester elastomer / TPE-E

Components	CAS-No	Percent %
Proprietary Filler A		20 - 50
Proprietary Filler B		20 - 50

Product name	CoolPoly®		NAGH/EN
MSDS number	87110055	Revision Date	Sep.11.2016***
Revision Number	0***	Issuing date	Oct.30.2017***

3. Composition/information on ingredients

TALC	14807-96-6	> 0.1
------	------------	-------

Remarks

This product may contain proprietary ingredients.

This is a polymeric material. Any hazardous constituents are wetted by the polymer system, and therefore are unlikely to present exposure under normal conditions of processing and handling.

4. First aid measures

Skin

Cool skin rapidly with cold water after contact with molten polymer. Do not peel solidified product off the skin. Immediate medical attention is required.

Eyes

Immediately flush eye(s) with plenty of water. Call a physician if irritation persists.

Inhalation

Move to fresh air in case of accidental inhalation of vapors. Get medical attention immediately if symptoms occur.

Ingestion

If swallowed, do not induce vomiting - seek medical advice.

Notes to physician

This product is essentially inert and nontoxic. However, if it is heated at too high a temperature or if it is burned, gases may be released. Patients who have been exposed to off-gases may need to have their arterial blood gases and carboxyhemoglobin levels checked. If the carboxyhemoglobin levels are normal, asphyxia (carbon dioxide replacing oxygen) is a possibility. As with any fire, irritant gases may have formed. If patients may have inhaled high concentrations of irritating fumes, they should be monitored for delayed onset pulmonary edema.

5. Fire-fighting measures

NFPA: Health: 1

Flammability: 0

Instability: 0

Suitable extinguishing media

Water, Foam, Dry powder, Carbon dioxide (CO₂)

Special exposure hazards arising from the substance or preparation itself, its combustion products, or released gases

Carbon monoxide

Carbon dioxide (CO₂)

Nitrogen oxides (NO_x)

Boron oxides

Special protective equipment for fire-fighters

Wear self-contained breathing apparatus and protective suit.

Other Information

Keep people away from and upwind of fire. Dust can form an explosive mixture in air

Product name	CoolPoly®	Revision Date	NAGH/EN
MSDS number	87110055	Issuing date	Sep.11.2016***
Revision Number	0***		Oct.30.2017***

6. Accidental release measures

Personal precautions

Avoid dust formation***

Environmental precautions

Do not flush into surface water or sanitary sewer system.

Methods for cleaning up

Use mechanical handling equipment. Dispose of in accordance with local regulations***

7. Handling and storage

Advice on safe handling

Do not handle hot or molten material without appropriate protective equipment. Do not exceed recommended process temperatures to minimize release of decomposition products. Maintain good housekeeping in work areas.. Provide appropriate exhaust ventilation at machinery and at places where dust can be generated***

Protection - fire and explosion:

Do not smoke in areas where polymer dust is present.. Appropriate measures should be taken to control the generation and accumulation of dust during conveying and processing operations..

Material storage

Keep in a dry, cool and well-ventilated place. Maintain dryness of resin.. Keep away from direct sunlight.

Incompatible products

oxidizing agents, reducing agents, strong acids

8. Exposure controls / personal protection

OSHA Exposure Limits

Components	TWA
Proprietary Filler A	15 mg/m ³ Total Dust; 5 mg/m ³ Respirable Dust
Proprietary Filler B	5 mg/m ³
TALC	20 mppcf

ACGIH Exposure Limits

Components	TWA
Proprietary Filler A	10 mg/m ³ Total Dust; 3 mg/m ³ Respirable Dust
Proprietary Filler B	5 mg/m ³
TALC	2 mg/m ³

Mexico National Exposure Limits

Components	LMPE - PPT
TALC	2 FIBERS/CM3

Product name	CoolPoly®		NAGH/EN
MSDS number	87110055	Revision Date	Sep.11.2016***
Revision Number	0***	Issuing date	Oct.30.2017***

Components	Mexican Carcinogen Category
TALC	A4

Exposure controls

Engineering measures

General: May not be adequate as the sole means to control employee exposure.
 Local Exhaust: Recommended when appropriate to control employee exposure to dust or process vapors***

Protective equipment

A safety shower and eyebath should be readily available.

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment

Skin protection:

When thermal or melt processing, wear long pants, long sleeves, well insulated gloves, and face shield when there is a chance of contact..

Eye/face protection:

Safety glasses with side-shields. Safety goggles.

Comments:

Operations involving grinding and machining of parts should be reviewed to assure that particulate levels are kept below recommended standards

9. Physical and chemical properties

Appearance

Form	pellets
Color	Not available
Odor	slight
Flash point	Not Determined
Autoignition Temperature	Not applicable
Ignition temperature	No data available
Decomposition Temperature	Not determined
Lower explosion limit	not applicable
Upper explosion limit	not applicable
VOC Content(%)	Not determined

10. Stability and reactivity

Product name	CoolPoly®		NAGH/EN
MSDS number	87110055	Revision Date	Sep.11.2016***
Revision Number	0***	Issuing date	Oct.30.2017***

Chemical stability

Stable under normal conditions

Conditions to avoid

Flame. Avoid prolonged heating at or above the recommended processing temperature.***

Incompatible Materials

- oxidizing agents
- reducing agents
- strong acids

Hazardous Combustion or Decomposition Products:

Carbon oxides, Boron oxides, Nitrogen oxides (NOx)

11. Toxicological information

Potential health effects

Routes of exposure Skin, eyes, inhalation, ingestion.

Immediate effects

- Skin** Polymer particles may cause mechanical irritation. The molten product can cause serious burns.
- Eyes** Resin particles, like other inert materials, are mechanically irritating to eyes
- Inhalation** Dust irritating to respiratory tract. Overheating in processing may generate hazardous, irritating vapours.
- Ingestion** Low toxicity by this route is expected based on the biological activity of high molecular weight polymers.

Medical conditions which may be aggravated by exposure: No specific information available on the product. Off-gases, which may be released if overheated, may affect those with chronic diseases of the respiratory system.

Toxicological data are not available. Observe the usual hygienic measures for handling chemicals.

12. Ecological Information

Ecotoxicity:The effects of resin pellets on the wildlife that may ingest them is not well understood. In the case of seabirds, some marine biologists believe that the fowl may not be able to pass plastic pellets through their digestive tracts. Thus, large quantities of ingested pellets may cause intestinal blockage, false feelings of satiation or reduction in absorption of nutrients, causing malnutrition and starvation. The goal of SPI's Operation Clean Sweep is zero loss of pellets into the environment..

Environmental Fate/Information:This material is considered to be non-biodegradable. Do not discharge product unmonitored into the environment***

Product name	CoolPoly®		NAGH/EN
MSDS number	87110055	Revision Date	Sep.11.2016***
Revision Number	0***	Issuing date	Oct.30.2017***

13. Disposal considerations

Disposal considerations

Recycling is encouraged. Dispose of spilled material in accordance with state and local regulations for waste that is non-hazardous by Federal definition. Note that this information applies to the material as manufactured; processing, use, or contamination may make this information inappropriate, inaccurate, or incomplete.

This product as shipped is not a RCRA hazardous waste under present EPA regulations

14. Transport information

US Department of Transportation Not regulated

TDG Not regulated

Mexico Transport Information Not regulated

ICAO/IATA Not restricted

IMDG Not regulated

15. Regulatory Information

US State Regulations

Chemicals associated with the product which are subject to the state right-to-know regulations are listed along with the applicable state(s):

TALC 14807-96-6

Pennsylvania	Listed
New Jersey	Listed
Illinois	Listed
Massachusetts	Listed
Rhode Island	Listed

U.S. FEDERAL REGULATIONS

TSCA Inventory:

This product complies with the U.S. Toxic Substances Control Act (TSCA).

Environmental Regulations:

SARA 313 Chemicals

Contains no substances at or above the reporting threshold under Section 313.

SARA 311:

Product name	CoolPoly®		NAGH/EN
MSDS number	87110055	Revision Date	Sep.11.2016***
Revision Number	0***	Issuing date	Oct.30.2017***

Acute health:	No
Chronic health:	No
Fire:	No
Sudden release of pressure:	No
Reactive:	No

INTERNATIONAL REGULATIONS

CANADIAN REGULATIONS

WHMIS Classification: Not a WHMIS controlled product.

WHMIS Ingredient Disclosure List IDL:

This product does not contain substances required to be disclosed according to the Canada WHMIS Ingredient Disclosure List.

16. Other information

NFPA:	Health: 1	Flammability: 0	Instability: 0
HMIS:	Health: 1	Flammability: 0	Physical Hazard: 0

Color code(s)
BLUE

Prepared By
Product Stewardship Department
Celanese

Sources of key data used to compile the datasheet

Information contained in this safety data sheet is based on Celanese owned data and public sources deemed valid or acceptable..

Other Information:

Observe national and local legal requirements

Except as otherwise noted, all of the trademarks referenced herein are owned by Ticona or its affiliates. ***

Changes against the previous version are marked by ***

This product is not intended for use in medical or dental implants.

The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. Celanese makes no warranty of any kind, express or implied, concerning the safe use of this material in your process or in combination with other substances. Effects can be aggravated by other materials and/or this material may aggravate or add to the effects of other materials. User has sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. User must meet all applicable safety and health standards.

Product name	CoolPoly®		NAGH/EN
MSDS number	87110055	Revision Date	Sep.11.2016***
Revision Number	0***	Issuing date	Oct.30.2017***

Abbreviation and Acronym:

ADR = Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

CAS = Chemical Abstracts Service (division of the American Chemical Society)

CLP = Classification, Labelling and Packaging

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial Chemical Substances

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk (IMO)

ICAO = International Civil Aviation Organization

IMDG = International Maritime Code for Dangerous Goods