

Product name CoolPoly® E2
MSDS number 870038
Revision Number 0

AGHS/EN

Revision Date Apr.23.2015
Issuing date Dec.04.2015***

1. Identification of the substance/preparation and the company/undertaking

Product name
CoolPoly® E2

The following SDS applies to products described by combinations of the following trade name, product grade and color code listed below.

Color Code:
See Section 16 for list of Color Codes***

Manufacturer or supplier's details

Celanese (Shanghai) International Trading Co., Ltd.
Room 239, Xinmao Building
South Taizhong Road
Waigaoqiao Free Trade Zone
Shanghai, China

Celanese Pte Ltd
138 Robinson Road
#17-00
Singapore (068906)

Product Information
info-engineeredmaterials-asia@celanese.com

Emergency telephone number
+(65) 62656917 (Operations Room direct dial)
or fax request to +(65) 62664696 (Facsimile to Operations Room)
or email to posh.er@paccoffshore.com.sg

In China Emergency Number: 86-532-83889090 (NRCC)

Synonyms:
Liquid crystal polymer / LCP

Identified uses
Plastic processing industry.

2. Hazards identification

Statements of Hazard Not a dangerous product according to GHS

3. Composition/Information on ingredients

Product name CoolPoly® E2
MSDS number 870038
Revision Number 0

AGHS/EN

Revision Date Apr.23.2015
Issuing date Dec.04.2015***

3. Composition/Information on ingredients

Chemical characterization Liquid crystal polymer / LCP, CAS-RN. basic polymer: 147310-94-9; Filament carbon fiber, CAS-RN.: 7440-44-0***

4. First aid measures

Skin
Cool skin rapidly with cold water after contact with molten polymer. Do not peel solidified product off the skin. Immediate medical attention is required.

Eyes
Immediately flush eye(s) with plenty of water. Call a physician if irritation persists.

Inhalation
Move to fresh air in case of accidental inhalation of vapors. Get medical attention immediately if symptoms occur.

Ingestion
If swallowed, do not induce vomiting - seek medical advice.

Notes to physician
This product is essentially inert and nontoxic. However, if it is heated at too high a temperature or if it is burned, gases may be released. Patients who have been exposed to off-gases may need to have their arterial blood gases and carboxyhemoglobin levels checked. If the carboxyhemoglobin levels are normal, asphyxia (carbon dioxide replacing oxygen) is a possibility. As with any fire, irritant gases may have formed. If patients may have inhaled high concentrations of irritating fumes, they should be monitored for delayed onset pulmonary edema.

5. Fire-fighting measures

NFPA: **Health:** 1 **Flammability:** 0 **Instability:** 0

Suitable extinguishing media
Water, Carbon dioxide (CO₂), Foam, Dry powder

Special exposure hazards arising from the substance or preparation itself, its combustion products, or released gases
Under conditions giving incomplete combustion, hazardous gases produced may consist of
Carbon monoxide
Carbon dioxide (CO₂)

Special protective equipment for fire-fighters
Wear self-contained breathing apparatus and protective suit.

Other Information
Keep people away from and upwind of fire. Dust can form an explosive mixture in air***

6. Accidental release measures

Personal precautions
Avoid dust formation.

Product name CoolPoly® E2
MSDS number 870038
Revision Number 0

AGHS/EN

Revision Date Apr.23.2015
Issuing date Dec.04.2015***

Environmental precautions

No special environmental precautions required.

Methods for cleaning up

Use mechanical handling equipment. Dispose of in accordance with local regulations***

7. Handling and storage**Advice on safe handling**

Do not handle hot or molten material without appropriate protective equipment. Do not exceed recommended process temperatures to minimize release of decomposition products. Maintain good housekeeping in work areas.. Provide appropriate exhaust ventilation at machinery and at places where dust can be generated***

Protection - fire and explosion:

Do not smoke in areas where polymer dust is present.. Appropriate measures should be taken to control the generation and accumulation of dust during conveying and processing operations.***

Material storage

Keep in a dry, cool place. Maintain dryness of resin.***

Technical measures/Storage conditions

No special technical protective measures required***

8. Exposure controls / personal protection**ACGIH Exposure Limits**

No exposure limits established.

Exposure controls**Engineering measures**

General: May not be adequate as the sole means to control employee exposure.
 Local Exhaust: Recommended when appropriate to control employee exposure to dust or process vapors***

Personal protective equipment**Hygiene measures**

When using, do not eat, drink or smoke. Do not inhale dust particles, during processing carbon fiber particles are set free and cause irritation to the respiratory passage.. Wash hands before breaks and at the end of workday..

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment.

Eye protection

safety glasses. Safety goggles.

Skin protection

Avoid contact with skin

Hand protection**Suitable material
Type**

protective gloves
 Butyl-rubber
 Butoject (Company KCL) or comparable article;
 or refer to glove manufacturer's recommendation

Evaluation**Material thickness**

according to EN 374: level 6
 approx. 0,3 mm

Product name CoolPoly® E2
 MSDS number 870038
 Revision Number 0

AGHS/EN

Revision Date Apr.23.2015
 Issuing date Dec.04.2015***

Break through time 480 min

9. Physical and chemical properties

Appearance

Form pellets
 Odor slight

Flash point Not applicable
 Ignition temperature No data available
 Density Not Determined
 Bulk density Not Determined
 Water solubility insoluble
 VOC Content(%) Not determined

10. Stability and reactivity

Chemical stability

Stable under normal conditions

Conditions to avoid

Flame.. Avoid prolonged heating at or above the recommended processing temperature.***

Incompatible Materials

None known

Hazardous Combustion or Decomposition Products:

Thermal decomposition products may include oxides of carbon.***

11. Toxicological information

Potential health effects

Routes of exposure Skin, eyes, inhalation, ingestion.

Immediate effects

Skin Polymer particles may cause mechanical irritation. The molten product can cause serious burns.***

Eyes Resin particles, like other inert materials, are mechanically irritating to eyes***

Inhalation Dust irritating to respiratory tract. Overheating in processing may generate hazardous, irritating vapours.***

Ingestion Low toxicity by this route is expected based on the biological activity of high molecular weight polymers.

Medical conditions which may be aggravated by exposure: No specific information available on the product. Off-gases, which may be released if overheated, may affect those with chronic diseases of the respiratory system.***

Product name CoolPoly® E2
MSDS number 870038
Revision Number 0

AGHS/EN

Revision Date Apr.23.2015
Issuing date Dec.04.2015***

Toxicological data are not available. Observe the usual hygienic measures for handling chemicals***

12. Ecological Information

Ecotoxicity:The effects of resin pellets on the wildlife that may ingest them is not well understood. In the case of seabirds, some marine biologists believe that the fowl may not be able to pass plastic pellets through their digestive tracts. Thus, large quantities of ingested pellets may cause intestinal blockage, false feelings of satiation or reduction in absorption of nutrients, causing malnutrition and starvation. The goal of SPI's Operation Clean Sweep is zero loss of pellets into the environment..

Environmental Fate/Information:This material is considered to be non-biodegradable.. Do not discharge product unmonitored into the environment***

13. Disposal considerations

Product information

Disposal required in compliance with all waste management related state and local regulations. The choice of the appropriate method of disposal depends on the product composition by the time of disposal as well as the local statutes and possibilities for disposal

Uncleaned empty packaging

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse

14. Transport information

US Department of Transportation Not regulated

ADR/RID Not regulated

ADN Not regulated

ICAO/IATA Not restricted

IMDG Not regulated

15. Regulatory information

INTERNATIONAL REGULATIONS

This preparation is not classified as dangerous according to Chinese legislation.

This mixture is not classified as dangerous according to Japanese legislation.

16. Other information

Product name CoolPoly® E2
MSDS number 870038
Revision Number 0

AGHS/EN

Revision Date Apr.23.2015
Issuing date Dec.04.2015***

16. Other information

HMIS: Health: 1

Flammability: 0

Physical Hazard: 0

Prepared By

Product Stewardship Department
Celanese

Other Information:

Observe national and local legal requirements. Except as otherwise noted, all of the trademarks referenced herein are owned by Ticona or its affiliates. .

Changes against the previous version are marked by ***

Sources of key data used to compile the datasheet

Information contained in this safety data sheet is based on Celanese owned data and public sources deemed valid or acceptable. The absence of data elements required by ANSI or 1907/2006/EC indicates that no data meeting these requirements is available.

Further information

This information is based on our present state of knowledge. It shall describe our products regarding safety requirements and shall not be construed as a guarantee or statement of condition and/or quality