

Product name	CoolPoly®		NAGH/EN
MSDS number	870023	Revision Date	May.16.2016
Revision Number	1	Issuing date	May.16.2016

1. Product and company identification

Trade Name

CoolPoly®

The following SDS applies to products described by combinations of the following trade name, product grade and color code listed below.

Product Grade(s):

D3612

Color Code:

See Section 16 for list of Color Codes

Manufacturer, importer, supplier

Ticona Polymer, Inc.

A business of Celanese

8040 Dixie Hwy.

Florence, KY 41042

United States

www.celanese.com

Transportation emergency phone numbers:

In USA, call 800 424 9300

Outside USA, call 703 527 3887, collect calls accepted.

Product Information

1-800-833-4882

info-engineeredmaterials-am@celanese.com

Synonyms:

Policapram

Identified uses

Plastic processing industry.

2. Hazard Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200:

This material is not hazardous under the criteria of the Federal OSHA Hazard Communication Standard (29CFR 1910.1200)

3. Composition/information on ingredients

Chemical characterization Polyamide (PA6); CAS-RN of the basic polymer: 25038-54-4

Components	CAS-No	Percent %
------------	--------	-----------

Product name	CoolPoly®		NAGH/EN
MSDS number	870023	Revision Date	May.16.2016
Revision Number	1	Issuing date	May.16.2016

3. Composition/information on ingredients

Proprietary Filler A		20 - 50
----------------------	--	---------

Remarks

This product may contain proprietary ingredients.
 This is a polymeric material. Any hazardous constituents are wetted by the polymer system, and therefore are unlikely to present exposure under normal conditions of processing and handling.

4. First aid measures

Skin

Cool skin rapidly with cold water after contact with molten polymer. Do not peel solidified product off the skin. Immediate medical attention is required.

Eyes

Immediately flush eye(s) with plenty of water. Call a physician if irritation persists.

Inhalation

Move to fresh air in case of accidental inhalation of vapors. Get medical attention immediately if symptoms occur.

Ingestion

If swallowed, do not induce vomiting - seek medical advice.

Notes to physician

This product is essentially inert and nontoxic. However, if it is heated at too high a temperature or if it is burned, gases may be released. Patients who have been exposed to off-gases may need to have their arterial blood gases and carboxyhemoglobin levels checked. If the carboxyhemoglobin levels are normal, asphyxia (carbon dioxide replacing oxygen) is a possibility. As with any fire, irritant gases may have formed. If patients may have inhaled high concentrations of irritating fumes, they should be monitored for delayed onset pulmonary edema.

5. Fire-fighting measures

NFPA: **Health:** 1 **Flammability:** 0 **Instability:** 0

Suitable extinguishing media

Water, Foam, Dry powder, Carbon dioxide (CO2)

Special exposure hazards arising from the substance or preparation itself, its combustion products, or released gases

- Carbon monoxide
- Carbon dioxide (CO2)
- Nitrogen oxides (NOx)
- Hydrogen cyanide (hydrocyanic acid)
- Oxides of phosphorus
- Boron oxides

Special protective equipment for fire-fighters

Wear self-contained breathing apparatus and protective suit.

Product name	CoolPoly®		NAGH/EN
MSDS number	870023	Revision Date	May.16.2016
Revision Number	1	Issuing date	May.16.2016

Other Information

Keep people away from and upwind of fire. Dust can form an explosive mixture in air.

6. Accidental release measures

Personal precautions

Avoid dust formation.

Environmental precautions

Do not flush into surface water or sanitary sewer system.

Methods for cleaning up

Use mechanical handling equipment. Dispose of in accordance with local regulations.

7. Handling and storage

Advice on safe handling

Do not handle hot or molten material without appropriate protective equipment. Do not exceed recommended process temperatures to minimize release of decomposition products. Maintain good housekeeping in work areas.. Provide appropriate exhaust ventilation at machinery and at places where dust can be generated.

Protection - fire and explosion:

Do not smoke in areas where polymer dust is present.. Appropriate measures should be taken to control the generation and accumulation of dust during conveying and processing operations..

Material storage

Keep in a dry, cool and well-ventilated place. Maintain dryness of resin..

8. Exposure controls / personal protection

OSHA Exposure Limits

Components	TWA
Proprietary Filler A	15 mg/m ³ Total Dust; 5 mg/m ³ Respirable Dust

ACGIH Exposure Limits

Components	TWA
Proprietary Filler A	10 mg/m ³ Total Dust; 3 mg/m ³ Respirable Dust

Mexico National Exposure Limits

No exposure limits established

Exposure controls

Product name	CoolPoly®		NAGH/EN
MSDS number	870023	Revision Date	May.16.2016
Revision Number	1	Issuing date	May.16.2016

Engineering measures

General: May not be adequate as the sole means to control employee exposure.
 Local Exhaust: Recommended when appropriate to control employee exposure to dust or process vapors.

Protective equipment

A safety shower and eyebath should be readily available.

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment

Skin protection:

When thermal or melt processing, wear long pants, long sleeves, well insulated gloves, and face shield when there is a chance of contact..

Eye/face protection:

Safety glasses with side-shields. Safety goggles.

Comments:

Operations involving grinding and machining of parts should be reviewed to assure that particulate levels are kept below recommended standards

9. Physical and chemical properties

Appearance

Form	pellets
Odor	slight
Flash point	Not applicable
Ignition temperature	No data available
Melting Point	> 220 °C (> 428°F)
Density	Not Determined
Bulk density	Not Determined
Specific Gravity	> 1
Water solubility	insoluble
VOC Content(%)	Not determined

10. Stability and reactivity

Chemical stability

Stable under normal conditions

Conditions to avoid

Flame Avoid prolonged heating at or above the recommended processing temperature.

Incompatible Materials

- strong oxidizing agents
- reducing agents
- strong acids
- strong bases

Product name	CoolPoly®		NAGH/EN
MSDS number	870023	Revision Date	May.16.2016
Revision Number	1	Issuing date	May.16.2016

Hazardous Combustion or Decomposition Products:

Nitrogen oxides (NOx), Carbon dioxide (CO2), Carbon monoxide, ammonia, aliphatic amines, amides, ketones, nitriles, hydrogen cyanide., Boron oxides

11. Toxicological information

Potential health effects

Routes of exposure Skin, eyes, inhalation, ingestion.

Immediate effects

- Skin** Polymer particles may cause mechanical irritation. The molten product can cause serious burns.
- Eyes** Resin particles, like other inert materials, are mechanically irritating to eyes
- Inhalation** Dust irritating to respiratory tract. Overheating in processing may generate hazardous, irritating vapours.
- Ingestion** Low toxicity by this route is expected based on the biological activity of high molecular weight polymers.

Medical conditions which may be aggravated by exposure: No specific information available on the product. Off-gases, which may be released if overheated, may affect those with chronic diseases of the respiratory system.

Toxicological data are not available. Observe the usual hygienic measures for handling chemicals.

12. Ecological Information

Ecotoxicity:The effects of resin pellets on the wildlife that may ingest them is not well understood. In the case of seabirds, some marine biologists believe that the fowl may not be able to pass plastic pellets through their digestive tracts. Thus, large quantities of ingested pellets may cause intestinal blockage, false feelings of satiation or reduction in absorption of nutrients, causing malnutrition and starvation. The goal of SPI's Operation Clean Sweep is zero loss of pellets into the environment..

Environmental Fate/Information:This material is considered to be non-biodegradable.. Do not discharge product unmonitored into the environment.

Product name	CoolPoly®		NAGH/EN
MSDS number	870023	Revision Date	May.16.2016
Revision Number	1	Issuing date	May.16.2016

13. Disposal considerations

Disposal considerations

Recycling is encouraged. Dispose of spilled material in accordance with state and local regulations for waste that is non-hazardous by Federal definition. Note that this information applies to the material as manufactured; processing, use, or contamination may make this information inappropriate, inaccurate, or incomplete.

This product as shipped is not a RCRA hazardous waste under present EPA regulations

14. Transport information

US Department of Transportation Not regulated

TDG Not regulated

Mexico Transport Information Not regulated

ICAO/IATA Not restricted

IMDG Not regulated

15. Regulatory Information

US State Regulations

Chemicals associated with the product which are subject to the state right-to-know regulations are listed along with the applicable state(s):

none

U.S. FEDERAL REGULATIONS

TSCA Inventory:

This product complies with the U.S. Toxic Substances Control Act (TSCA).

Environmental Regulations:

SARA 313 Chemicals

Zinc Compounds (1-60 wt%)

SARA 311:

Acute health:	No
Chronic health:	No
Fire:	No
Sudden release of pressure:	No
Reactive:	No

Product name	CoolPoly®		NAGH/EN
MSDS number	870023	Revision Date	May.16.2016
Revision Number	1	Issuing date	May.16.2016

INTERNATIONAL REGULATIONS

CANADIAN REGULATIONS

WHMIS Classification: Not a WHMIS controlled product.

WHMIS Ingredient Disclosure List IDL:

Zinc Oxide (1314-13-2)

16. Other information

NFPA:	Health: 1	Flammability: 0	Instability: 0
HMIS:	Health: 1	Flammability: 0	Physical Hazard: 0

Color code(s)

NATURAL

Prepared By

Product Stewardship Department
Celanese

Sources of key data used to compile the datasheet

Information contained in this safety data sheet is based on Celanese owned data and public sources deemed valid or acceptable..

Other Information:

Observe national and local legal requirements

Except as otherwise noted, all of the trademarks referenced herein are owned by Ticona or its affiliates.

Changes against the previous version are marked by ***

This product is not intended for use in medical or dental implants.

The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. Celanese makes no warranty of any kind, express or implied, concerning the safe use of this material in your process or in combination with other substances. Effects can be aggravated by other materials and/or this material may aggravate or add to the effects of other materials. User has sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. User must meet all applicable safety and health standards.

Abbreviation and Acronym:

ADR = Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

CAS = Chemical Abstracts Service (division of the American Chemical Society)

CLP = Classification, Labelling and Packaging

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial Chemical Substances

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk (IMO)

ICAO = International Civil Aviation Organization

IMDG = International Maritime Code for Dangerous Goods