

# Acetic Acid Chemical Grade, 80 %

CAS-No. 64-19-7

## Sales Specification

Specifications <sup>(1)</sup>		Limit	Unit
Acetic Acid		79.5 – 80.5	wt. %
Color	max.	5	Pt-Co
Permanganate Time / Oxidizable Impurities	min.	2	hours
Density at 20 °C <sup>(2)</sup>	-	1.069 – 1.071	g/cm <sup>3</sup>
Appearance	-	CFSM <sup>(3)</sup>	-

(1) Test methods available upon request.

(2) Product conforms to limit, but test is not routinely performed.

(3) Clear and Free from Suspended Matter.

Acetic Acid, Chemical Grade 80 % is produced by dilution of Acetic Acid, Chemical Grade 99/100 % with demineralized water. Further inspection characteristics can be derived from the Celanese Sales Specification for Acetic Acid, Chemical Grade 99/100 %.

Product Numbers: 50001436

Spec. HACCHEM80-006-EMEA-Jun25

Supersedes: AceticAcidChem80\_50001436\_SLS\_e\_V5 of November 15, 2016 (Version-No. 5)

Celanese Performance Solutions Switzerland Sàrl  
Route du Nant-d'Avril 146,  
1217 Meyrin,  
Switzerland  
T+41 22 717 69 00

The information contained in this publication is based on our present state of knowledge and is intended to provide general notes on our products and their uses. It should not be construed as warranting or guaranteeing specific properties of the products described or their suitability for a particular application. User is solely responsible for determining the suitability of the products for the intended purpose. To the best of our knowledge the information in this publication is accurate; however, we do not assume any liability whatsoever for the accuracy and completeness of such information. We strongly recommend that users seek and adhere to our current instructions for handling these products, and to entrust the handling of such products to adequately trained personnel only. Please adhere to the instructions and information contained in the corresponding Safety Data Sheets (SDS) before attempting to process our products. Any existing industrial property rights must be observed. User is solely responsible for investigating and checking the regulatory approval status.