

Isobutyric Anhydride

Product Quality, Regulatory & Technical Information Package

June 2025


Product Name: Isobutyric Anhydride

Chemical Name: Isobutyric Anhydride

CAS number: 97-72-3

Celanese (bulk) Material number: 50000431

The Product is also available from Celanese as packed goods in IBC and drums.



Disclaimer

Celanese is supplying Isobutyric Anhydride as a technical grade product.

This document provides information about technical grade Isobutyric Anhydride ("Product") produced by Celanese and its affiliates ("Celanese" or "we"). The information presented in this document is based on our present state of knowledge and is intended to provide general notes on the Product and its intended uses. It does not constitute a guarantee of any specific properties of the Products described herein or its suitability for a particular application. The customer must make the sole determination whether the Product is suitable for the desired use. Celanese undertakes no obligation to update the information in this document.

The practice of providing this information to customers is for their convenience and is not legally binding. It does not alter the terms and conditions of sale, including without limitation, any limits of liability, applicable to the underlying commercial transaction involving the Product(s) to which this information applies. The Information is intended for use by persons having skill with respect to the subject matter involved.

Celanese makes no warranties, express or implied, and assumes no liability for the accuracy or completeness or in connection with any use of this information. Nothing herein is intended as a license to operate under or a recommendation to infringe any patents.

General

Further literature to the Product, such as Safety Data Sheet, Brochures and Specifications can be retrieved from Celanese website www.celanese.com.

Isobutyric Anhydride
Product Quality, Regulatory & Technical Information Package
 June 2025

Table of Contents

Disclaimer	1
General	1
Table of Contents	2
Product Description	3
Physical properties	3
Storage and Handling Recommendations	4
<i>Storage</i>	4
<i>Handling</i>	4
<i>Materials of Construction</i>	5
Product Quality Statements	6
<i>Manufacturing Locations</i>	6
<i>ISO Certification</i>	6
<i>Specification</i>	6
<i>Analytical Methods</i>	6
<i>Manufacturing Process & Raw Materials</i>	7
<i>Shelf Life</i>	7
<i>Kosher</i>	7
<i>Halal</i>	7
<i>ICH Guidelines</i>	8
<i>Radiation</i>	8
Regulatory Statements	8
<i>Animal Testing</i>	8
<i>BSE/TSE</i>	8
<i>Genetically Modified Organisms (GMO)</i>	8
<i>Global Country Inventories</i>	8
<i>Allergens</i>	9
<i>Excluded substances</i>	9
<i>EU REACH</i>	10
<i>Food & Food Contact</i>	11
<i>Restriction of Hazardous Substances (RoHS)</i>	11
<i>Volatile Organic Compounds (VOC)</i>	12
Attachment I: Sales Specifications	13

Isobutyric Anhydride

Product Quality, Regulatory & Technical Information Package

June 2025

Product Description

Isobutyric Anhydride is a clear, colorless liquid with an unpleasant, rancid odor. It is miscible in any proportion with most organic solvents. The product hydrates with water and decomposes with alcohol.

Isobutyric Anhydride may be used as an acylating agent, e.g. in the production of dyes, agrochemicals and other chemicals. It also may be used in the production of cellulose iso-butyrate and cellulose acetate iso-butyrate.

Physical properties

Data are intended for the purpose of product description and are not the subject of continuous monitoring. Further physical properties and characteristic data as well as information on safety and handling are listed in the safety data sheet and the sales specifications. Please consult www.celanese.com.

Property	Metric Units	English Units
Boiling Point @ 101.3 kPa (14.69 psi)	182.9 °C	361.2 °F
Density @ 20 °C (68 °F) (DIN 51 757)	0.952 g/cm ³	7.945 lb/gal
Melting Point	- 55 °C	- 67 °F
Molar Mass	158.22 g/mole	
Refractive index n _D ²⁰ (68 °F) (DIN 51 423, part 2)	1.405 – 1.407	
Solubility in Water @ 20 °C (68 °F)	hydrolyses	
Surface Tension @ 21.4 °C (70.5)	26.32 mN/m	
Vapor pressure @ 20 °C (68 °F)	0.86 hPa	0.012 psi
Viscosity @ 25 °C (77 °F)	1.23 mPa · s	

Isobutyric Anhydride

Product Quality, Regulatory & Technical Information Package

June 2025

Storage and Handling Recommendations

Storage

Recommended Blanketing	Dry Air ^{a, b} or Dry Nitrogen ^{a, b, c}
Recommended Temperature	
Maximum	37.8 °C (100 °F)
Minimum	- 17.8 °C (0 °F)
Recommended pressure	Atmospheric
Bulk Quantities	Outside, detached tanks
Small Containers	Cool, dry, well ventilated area

- Refer to National Fire Protection Agency (NFPA) #77 "Static Electricity" or the respective national technical code for proper electrical grounding procedures.
- See the National Fire Protection Agency (NFPA) #30 "Flammable and Combustible Liquids Code" or the respective national technical code and consult with qualified fire protection specialists to determine specific storage tank design requirements.
- Blanketing may be used to retain quality in long-term storage conditions.

Handling

- Thoroughly review Safety Data Sheet before handling product.
- Keep containers closed when not in use.
- Open containers slowly to allow any excess pressure to vent.
- Keep away from heat, sparks, flame or other sources of ignition.
- Protect small containers from physical damage.
- Use proper electrical grounding and bonding procedures when loading, unloading and transferring. Refer to the National Fire Protection Agency (NFPA) #77 "Recommended Practice for Static Electricity" or the respective national technical code for proper electrical grounding procedures.
- Use spark-resistant tools.
- Electrical equipment and circuits in all storage and handling areas must conform to requirements of national electrical code (Articles 500 and 501) or the respective national technical code for hazardous location.
- Refer to Safety Data Sheet for more information on materials to avoid.
- For further information on safety and handling, please use the following link:
<https://www.celanese.com/sds-search>

Isobutyric Anhydride

Product Quality, Regulatory & Technical Information Package

June 2025

Materials of Construction

Unit / element	Acceptable Material	Alternate Material
Tank	Stainless Steel ^a	Aluminum ^{b, d}
Piping	Stainless Steel ^a	Aluminum ^{b, d}
Valves	Stainless Steel ^a	Aluminum ^{b, d}
Pumps	Stainless Steel ^a	–
Relief Valves	Stainless Steel ^a	–
Gaskets	PTFE ^e	Butyl Rubber
Pump Seals	Single Mechanical Seal: Stainless Steel / Hastelloy C-276 metallic components, Kalrez O-rings	–
Valve Packing	PTFE ^e	–
Pipe End Connections	Welded and flanged system	Threaded with PTFE ^e tape thread lubricant
Heat Exchanger	Product side: Stainless Steel ^a	–
Hoses	Stainless Steel ^a	–
Tank Truck	Stainless Steel ^a	Aluminum ^{b, d}
Tank Car	Stainless Steel ^a	Aluminum ^{b, d} Lined Carbon Steel ^c
Barge	Stainless Steel ^a	–
Ship Tank	Stainless Steel ^a	–

- a. Type 304 or 316 Stainless Steel
- b. Type 3000, 5000 and 6000 series Aluminum when the temperature does not exceed 49 °C (120 °F).
- c. Lining refers to high baked phenolic resin.
- d. May be used if no moisture is present.
- e. Polytetrafluoroethylene

Isobutyric Anhydride

Product Quality, Regulatory & Technical Information Package

June 2025

Product Quality Statements

Manufacturing Locations

The Product is produced at manufacturing location in Frankfurt (Germany).

- Industrial Park Frankfurt-Hoechst
 Brueningstr. 50
 65926 Frankfurt
 Germany

ISO Certification

The Product is a technical grade material produced under ISO 9001 rules. Certificates are available at Celanese web page (Select Filter "Intermediate Chemistry" and additional filters to retrieve the Certificate from the respective Manufacturing site):

<https://www.celanese.com/certificate-search>

Specification

The Product is supplied according to Celanese Sales Specification. A copy of the Sales Specification is attached to this dossier.

1. Celanese has a product traceability and withdrawal/recall program in place which we believe is appropriate for technical grade products.
2. The Product is not manufactured under GMP rules.
3. Celanese makes no nutrition statement.
4. There is no food or pharmaceutical grade hazard assessment program available for the Product.

Analytical Methods

Applied analytical methods according to the sales specifications provided as attachment.

Specifications	Analytical Methods ⁽¹⁾
Isobutyric Anhydride	DIN 51 405 (GC)
Isobutyric Acid	DIN 51 405 (GC)
Acetic Isobutyric Anhydride	DIN 51 405 (GC)
Acetic Anhydride	DIN 51 405 (GC)
Color	DIN EN 1557 / DIN ISO 6271 / ASTM D 1209 / ASTM 5386
Appearance	Visual Examination

¹ Alternative equivalent methods can be used at Celanese Terminals.


Isobutyric Anhydride

Product Quality, Regulatory & Technical Information Package

June 2025

Manufacturing Process & Raw Materials

Celanese produces the Product according to the chemical equation:



Isobutyric Acid is converted to Isobutyric Anhydride using Acetic Anhydride and removing Acetic Acid. The crude Anhydride is purified via distillation.

No metal, metal-organic or biological/protein based catalysts are being used in the production of the Product.

Celanese does not use raw materials of animal origin. During the manufacturing process, the material does not come into contact with materials of animal origin.

Shelf Life

The shelf life of the Product is one year.

The shelf life dates from the date of packaging, and for bulk deliveries this is the date of loading. This period is in general applicable to material

- packaged in discrete containers such as drums or bulk containers and
- stored under conditions recommended by Celanese.

For the Product this entails storage at ambient temperatures in tightly sealed, undamaged containers in a cool and well-ventilated place under dry air or dry nitrogen blanket. Blanketing may be used to retain quality in long term storage conditions, especially to prevent access of humidity.

Most products will have a longer useful life, but should be examined by the owner at its sole responsibility at the end of the recommended storage life to determine purity and condition of product. Bulk storage life, under recommended storage conditions, may be longer if the Product is routinely monitored for specific indications of the condition of the material, or if the Product in the tank is removed and replenished with fresh material on a routine basis. Any use of the Product after expiration of the shelf life is the sole responsibility of the buyer.

Kosher

A Kosher grade is available in some countries. Special shipping arrangements must be made in advance. Contact your Sales Representative for more information.

Halal

The Product is not available as a certified Halal grade.

Celanese supplies basic chemicals. Our production technology relies on a continuous production process, and the raw materials are of petrochemical origin. All catalysts and processing aids are of synthetic origin; we do not use any raw materials having an animal (diary) origin, nor is our process likely to be contaminated by such. Ethanol is not used as raw material or processing aid.

Isobutyric Anhydride

Product Quality, Regulatory & Technical Information Package

June 2025

ICH Guidelines

The Product does not, based on Celanese's knowledge, contain solvents in the concentration limits specified by the ICH Guideline Q3C(R9) for residual solvents.

The Product does not contain intentionally added sources of biological substances as described in ICH: Q5A (R2): Viral safety evaluation of biotechnology products derived from cell lines of human or animal origin.

Radiation

The Product is not subjected to any artificial radiation.

Regulatory Statements

Animal Testing

The Product was not subject of animal testing for cosmetic purposes by or on behalf of Celanese in order to meet the requirements of Regulation (EC) No 1223/2009 on cosmetic products.

As a chemical products manufacturer and importer, Celanese is required to participate in the chemical industry's efforts to ensure the protection of human health and the environment, and also has obligations under the REACH regulation (Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorization and Restriction of Chemicals).

Celanese practice is to extensively search internally and externally for existing toxicological information before initiating testing. Where existing information does not exist for relevant endpoints, a comprehensive effort will be made to avoid the use of animals by employing alternative methods. When other means have been exhausted and animal testing may be required to develop data to ensure the protection of health and the environment, scientifically sound techniques to reduce the numbers of animals will be used. All applicable animal welfare laws will be followed to ensure care and compassion are exercised.

BSE/TSE

The Product is not derived from human or animal sources and thus we are not aware of any BSE/TSE.

Genetically Modified Organisms (GMO)

The chemistry to manufacture the Product does not use genetically modified or engineered organisms or biomaterials. No GMO/GME substances are added to the Product.

Global Country Inventories

The substance is listed in the following country inventories:

Chemical Inventory Status	listed	comments
Australia (AIC)	yes	

Isobutyric Anhydride

Product Quality, Regulatory & Technical Information Package

June 2025

Chemical Inventory Status	listed	comments
Canada (DSL)	yes	
China (IECSC)	yes	
Japan (ENCS)	yes	
New Zealand (NZIOC)	yes	
Philippines (PICCS)	yes	
USA (TSCA)*	yes	active
Korea (KECI)	yes	
Taiwan (TCSI)	yes	
Mexico (INSQ)	yes	

* It is not subject to any action under TSCA Section 4, 5, 6, 8a, 8d, or 12b.

Allergens

The Product does not, based on Celanese's knowledge, contain the following substances and products thereof commonly associated with food allergens:

- Peanut
- Soya
- Bean
- Milk
- Egg
- Fish
- Peas
- Barley
- Lupine
- Molluscs
- Sulfur Dioxide
- Sulphites
- Tree nuts
- Wheat
- Crustaceans
- Gluten
- Glycerol
- Mustard

Excluded substances

These substances are not, based on Celanese's knowledge, present in the Product. They are not known to be generated in the production process, nor are we aware of such substances appearing as impurities in the raw materials. However, we do not have a specification for those substances, nor do we analyze for them.

Normal trace levels of metals may be found in the product.

- 2,4,6-Tris(tert-butyl)phenol (2,4,6-TTBP)
- 3-iodo-2-propynyl butylcarbamate (IBPC)
- Aflatoxins
- Algaecide / biocide
- Alkyl phenol ethoxylates (APEO) and their derivatives
- Amines
- Aromatic amines
- Aromatic hydrocarbons
- Asbestos
- Azo compounds
- Naphthalene
- Natural Latex
- Nitrates
- Nitrogen oxide
- Nitrosamines
- Nitrosating agents
- NOGE (novolac glycidyl ether)
- Organotin compounds
- Ortho phenyl phenol (OPP)
- Ozone depleting substances
- Palm Oils / Palm Kernel Oils

Isobutyric Anhydride

Product Quality, Regulatory & Technical Information Package

June 2025

- BADGE (2,2-bis(4-hydroxyphenyl)propane bis(2,3-epoxypropyl) ether)
- BFDGE (bis(hydroxyphenyl)methane bis(2,3-epoxypropyl) ethers)
- Bisphenol A
- Bisphenol F
- Brominated flame retardants
- Coloring Agents / Dyes
- Crystalline silica and leucophyllite minerals
- Cytokines
- Decabromodiphenyl ether (DecaBDE)
- Dioxins
- Epoxy compounds
- Ethylene oxide
- Flame retardants
- Fluorochemicals
- Glycol ethers
- Gold
- Halogenated solvents
- Heavy metals
- Hexachlorobutadiene (HCBD)
- Hybridoma cells
- Isothiazolinone compounds
- Jatropa
- Melamine
- Microplastics
- Mineral Oil Aromatic Hydrocarbons (MOAH)
- Mineral Oil Saturated Hydrocarbons (MOSH)
- Monoclonal antibodies
- N-(3-aminopropyl)-N-dodecylpropane-1,3-diamine
- Nanomaterials per US EPA definition
- Nanoparticle-based protein Therapeutics
- Paradichlorobenzene (PDCB)
- Pentachlorothiophenol (PCTP)
- Per- and polyfluoroalkyl substances (PFAS)²
- Pesticides
- Phenol, isopropylated phosphate (PIP (3:1))
- Phosphates
- Phthalates
- Pigments
- Plasticizers
- Polybrominated substances
- Polychlorinated substances
- Polyvinyl chloride (PVC)
- Protein subunits
- Pyridine
- Quaternary ammonium compounds
- Radioactive substances
- Resins
- Sewer sludge
- Shellac
- Silicones
- Subunit vaccines from in-vitro cell culture
- Tantalum
- Tin
- Titanium dioxide
- Tribromophenol
- Triclosan
- Tris (nonylphenyl) phosphite
- Tungsten
- Vinyl Chloride
- Viral vectors and Viral vector derived products
- Zinc oxide
- Zinc pyrithione

EU REACH

Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Celanese is aware of the obligations imposed by REACH on EU manufacturers and importers as well as on downstream users.

We are obliged to comply with the requirements of the REACH legislation relating to our European manufacturing facilities, our own imports as well as our obligations as a downstream user in the European chemical industry.

Should you require additional information on REACH and SVHC, please contact Celanese at REACH@celanese.com.

² PFAS as defined by the OECD: PFAS definition published by Organization for Economic Co-operation and Development (OECD) provided at this [LINK](#) (last accessed on 25 July 2024) or via DOI 10.1787/e458e796-en

Isobutyric Anhydride

Product Quality, Regulatory & Technical Information Package

June 2025

Food & Food Contact

Celanese produces and offers the Product exclusively as a technical product. The Product is not of a Food or Food contact grade. Any suitability for use is the sole responsibility of the buyer to verify fitness of the Product for the intended use and fitness of the final good for introduction into the market and to ensure compliance of the final goods with the relevant regulations.

Packaging Inks in Swiss Ordinance of the FDHA on Materials and Articles (817.023.21)

Status: 21st January 2021

Packaging inks are regulated in the section 12 of the Ordinance of the FDHA on Materials and Articles, and the provisions of this Section apply to packaging inks as specific constituent elements of materials and articles.

General listings in Annex 2 and Annex 10 to the Swiss Ordinance of the FDHA on Materials and Articles (817.023.21):

Annex 2
Not listed

Annex 10

1	Nr.	256
2	Bezeichnung des Stoffes	Isobutyric anhydride
3	CAS-Nr.	0000097-72-3
4	Ref-Nr.	
5	Verwendung	M
6	Teil	B
7	SML [mg/kg]	

Restriction of Hazardous Substances (RoHS)

Directive 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment (recast) (RoHS)

Status: 21st January 2021

The Product as supplied by Celanese does not fall within the scope of directive 2011/65/EU, since it applies to electrical and electronic equipment (EEE) "falling within the categories set out in Annex I." (Art. 2)

Annex II of Directive 2011/65/EU lists "Restricted substances [...] and maximum concentration values tolerated by weight in homogeneous materials"

- Lead (0.1 %)
- Mercury (0.1 %)
- Cadmium (0.01 %)
- Hexavalent chromium (0.1 %)
- Polybrominated biphenyls (PBB) (0.1 %)
- Polybrominated diphenyl ethers (PBDE) (0.1 %)
- Bis(2-ethylhexyl) phthalate (DEHP) (0,1 %)
- Butyl benzyl phthalate (BBP) (0,1 %)

Isobutyric Anhydride

Product Quality, Regulatory & Technical Information Package

June 2025

- Dibutyl phthalate (DBP) (0,1 %)
- Diisobutyl phthalate (DIBP) (0,1 %)

The Product, based on Celanese's knowledge, does not contain these substances at the required limits. However, these substances are not routinely tested in our analytical procedures and quality control system, therefore, analytical data on the existence/non-existence of these substances cannot be provided.

Volatile Organic Compounds (VOC)

Status: 21st January 2021

The Product fulfills the criteria and is considered a VOC according to

- 2010/75/EU on industrial emissions (integrated pollution prevention and control) (Recast)
- 2004/42/CE on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products (Paints Directive)
- Swiss OVOC, Ordinance on the Incentive Tax on Volatile Organic Compounds 814.018

Isobutyric Anhydride

Product Quality, Regulatory & Technical Information Package

June 2025

Attachment I: Sales Specifications

Isobutyric Anhydride

CAS-No. 97-72-3

Sales Specification

Specifications ⁽¹⁾		Limit	Unit
Isobutyric Anhydride	min.	98.0	wt. %
Isobutyric Acid	max.	2.0	wt. %
Acetic Isobutyric Anhydride	max.	0.30	wt. %
Acetic Anhydride	max.	0.10	wt. %
Color	max.	20	Pt-Co
Appearance	-	CFSM ⁽²⁾	-

(1) Test methods available upon request.

(2) Clear and Free from Suspended Matter.

Product Numbers: 50000431

Additional Product numbers in use for other packaging. Please contact your Sales Support.

Spec. iBAA-001-Global-Jun25

Supersedes: IsobutyricAnhydride_50000431_SLS_e_V5 of November 15, 2016 (Version-No. 5)

Celanese Performance
 Solutions Switzerland Sàrl
 Route du Nant-d'Avril 146,
 1217 Meyrin,
 Switzerland
 T+41 22 717 69 00

Celanese Pte Ltd
 Celanese Singapore Pte Ltd
 70 Anson Road
 #21-01/02
 Hub Synergy Point
 Singapore 079905
 T+65-6513-0443

Celanese Sales U.S. Ltd.
 222 W. Las Colinas Blvd.
 Suite 900N
 Irving TX 75039 U.S.A.
 T +1-972-443-4000

Celanese (Shanghai)
 International Trading Co. Ltd.
 Room 411, No. 473
 Fute West 1st Road
 Waigaoqiao Free Trade Zone
 Shanghai, China
 T +86-21-38619288

The information contained in this publication is based on our present state of knowledge and is intended to provide general notes on our products and their uses. It should not be construed as warranting or guaranteeing specific properties of the products described or their suitability for a particular application. User is solely responsible for determining the suitability of the products for the intended purpose. To the best of our knowledge the information in this publication is accurate; however, we do not assume any liability whatsoever for the accuracy and completeness of such information. We strongly recommend that users seek and adhere to our current instructions for handling these products, and to entrust the handling of such products to adequately trained personnel only. Please adhere to the instructions and information contained in the corresponding Safety Data Sheets (SDS) before attempting to process our products. Any existing industrial property rights must be observed. User is solely responsible for investigating and checking the regulatory approval status.